

European
Ceramics

LIMESTONE RANGE

Product Name: **LIMESTONE - VARIOUS COLOUR/FINISHES**

Product Identifier: Refer to tile name and product code on paperwork/packaging

Product Description: A glazed porcelain tile and a water absorption rate of less than 0.50%.

Country Of Origin: Italy

Building Code Obligations

Code Clauses:

B2 – Durability

B2.3.1

C3 – Fire affecting areas beyond the source

D1 – Access routes

D1.3.3

E3 – Internal moisture

E3.3.2, 3.3.3, 3.3.4

G3 – Food preparation and prevention of contamination

G3.3.2

G6 – Airborne and Impact sound

G6.3.1



Note – this building product is not subject to a warning/ban under section 26 of the Building Act 2004

Manufacturer Details:
European Ceramics Approved
BPIR COMPLIANT

Importer Details:
European Ceramic Tiles Ltd
Address: 7A Cowley Place, Rosedale, AKL 0632
NZBN: 9429037294571
Website: euroceramics.co.nz

Scope	Use
B2 Durability	See below suitability table
C3 Fire	The Building Code relating to fire ratings regulation & standards become mandatory from April 2013, establishing the list of products belonging to Classes A 'No Contribution to Fire' provided for in Decision 94/611/EC implementing Article 20 of Council Directive 89/106/EEC.
D1 Access Routes	Refer to slip resistance documentation for all Access routes classifications D1/AS1 for above range.
E3 Internal Moisture	Under E3 Tiles installed over a waterproof membrane using a nonporous grouting system, are an acceptable solution.
G3 Food Preparation & Prevention from Contamination	As an impervious and easy to clean surface, this range complies.
G6 Airborne & Impact Sound	If required, tiles can form part of an acoustic system to comply with IIC & STC in conjunction with an approved third-party system.

Suitability *	Residential	Light Commercial	Commercial
Indoor Floor	*	*	*
Indoor Walls	*	*	*
Outdoor Cladding	*	*	*
Frost Resistant	*	*	*
Swimming Pool Submerged	*	*	*
Swimming Pool Surround	*	*	*
Paving/External	*	*	*
Over Underfloor Heating	*	*	*
Kitchen wall	*	*	*
Within 1.5m of a Plumbing Fixture or Fitting	*	*	*

Manufacturer Details:
European Ceramics Approved
BPIR COMPLIANT

Importer Details:
European Ceramic Tiles Ltd
Address: 7A Cowley Place, Rosedale, AKL 0632
NZBN: 9429037294571
Website: euroceramics.co.nz

Building Code References

B2 – Durability

Compliance with B2 Durability is about providing evidence that the product will meet the relevant durability life in the context of the environment in which it will be located.

The building code sets out the framework for establishing the relevant durability life of building elements based on a number of criteria. B2/AS1 provides a decision tree to establish the relevant durability for common building materials in different circumstances.

Having determined the durability life of the product, the next step is to determine if the product, when exposed to the environment, will continue to perform for the relevant period. A key tool which a product supplier can consider in claiming compliance is limiting the environment in which the product will be exposed to (e.g. a ferrous material used in an indoor environment will last longer than it would when exposed to salt spray — in this example it would be appropriate for the supplier to condition the compliance information to use only in indoor environments).

C3 – Fire affecting areas beyond the source

C3 Fire affecting areas beyond the fire source is primarily about ensuring that fire does not spread from a fire in the building (in both vertically and horizontally) and from an adjacent building.

The prime product attribute used is the fire resistance rating (FRR) methodology. In most cases a product is combined with other products to achieve a FRR (e.g. an external wall fire rating may be formed by the combination of the external cladding, thermal insulation and the internal lining).

C/AS1 and C/AS2 set out performance criteria for buildings and in particular the FRR requirements for various types of buildings and parts of buildings. Appendix C of C/AS2 sets out test methods for the building elements involved in spread of fire. Appendix B of C/AS2 sets out performance criteria for sprinkler systems while Appendix A sets out criteria for fire safety systems such as alarms and hydrants.

D1 – Access routes

For D1 access routes, in most cases product-related compliance for access routes is slip resistance for floors and the shapes/locations etc of handrails. The Acceptable Solution for access D1/AS1 and NZS 4121:2001 provide good information on compliance for products on access routes.

E3 – Internal Moisture

E3 Internal Moisture is about ensuring that moisture created within the building does not lead to mould or create damage to adjacent buildings or structural elements in the building in which it is installed.

Prevention of the creation of mould is a combination of temperature, insulation and ventilation. Prevention of water damaging other building elements is mainly about installation details (i.e. sealing joints) as well as impervious products. E3/AS1 provides some useful design details, albeit without much product material information.

Manufacturer Details:
European Ceramics Approved
BPIR COMPLIANT

Importer Details:
European Ceramic Tiles Ltd
Address: 7A Cowley Place, Rosedale, AKL 0632
NZBN: 9429037294571
Website: euroceramics.co.nz

G3 – Food preparation and prevention of contamination

G3 Food preparation and prevention from contamination for a product (such as a kitchen bench) is mainly associated with being easily cleaned and impervious. G3/AS1 provides some general design details for food preparation areas but has no referenced product standards, although the document does state some acceptable materials used for surfaces. Compliance with G3/AS1 is not mandatory but provides a good benchmark for compliance.

G6 – Airborne and Impact Sound

For a product, G6 Airborne and impact sound is generally about systems which are designed to work together to achieve the necessary sound attenuation.

The code itself at G6.3.2 sets a quantifiable performance level: “The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55” and G6.3.2 sets the impact insulation class of floors shall be no less than 55. The Acceptable Solution G6/AS1 sets out the transmission and impact insulation class of common wall systems. G6/VM1 sets out test methodologies where the details do not match those of G6/AS1.

Manufacturer Details:
European Ceramics Approved
BPIR COMPLIANT

Importer Details:
European Ceramic Tiles Ltd
Address: 7A Cowley Place, Rosedale, AKL 0632
NZBN: 9429037294571
Website: euroceramics.co.nz

Technical Information




INFORMAZIONI TECNICHE | TECHNICAL INFORMATIONS

Gres porcellanato - Rettificato | Porcelain Stoneware - Rectified


















 V2 Moderate	 Heavy Traffic Traffico Intenso				
 Bending Strength	 Frost Resistance	 Chemicals Resistance	 Stain Resistance		
 R10 / A+B StrideUp	 Pendulum Ptv > 36 StrideUp	 Ansi A326.3 > 0,42 StrideUp	 Ansi A326.3 > 0,42 Naturale / Matte	 R11 / A+B+C Antislip Dehors	 Ansi A326.3 > 0,42 Antislip / Dehors
■ Fascia prezzo al mq. Price band per m ²		● Fascia prezzo al pezzo Price band per piece			

Gres porcellanato - Rettificato | Porcelain Stoneware - Rectified

NATURALE | MATTE - 6 MM THICK

IMBALLI PACKING	IMBALLO PACKAGING	M ² KG LASTRA / SLAB	IMBALLO PIENO FULL PACKAGING	IMBALLO VUOTO EMPTY PACKAGING
 120x280x0,6 cm 47 ^{11/16} x110 ^{13/16} x1/4"	 CASSA CRATE L 145 x P 292 x H 34	M ² 3,86 KG 48,60	M ² 67,20 KG 1.062,00 PZ 20	KG 90,00
	 CAVALLETTO A-FRAME L 75 x P 285 x H 153	M ² 3,36 KG 48,60	M ² 147,84 KG 2.318,40 PZ 44	KG 180,00

IMBALLI | PACKING
9 MM - 20 MM THICK

	THICK	PCS BOX	M ² BOX	KG BOX	BOX PALLET	M ² PALLET	KG PALLET
 FONDO StrideUp 160x80 62 ^{11/16} x31 ^{11/16} "	9mm	2	2,56	50,78	18	46,08	934,09
 FONDO StrideUp 120x120 47 ^{11/16} x47 ^{11/16} "	9mm	2	2,88	58,86	18	51,84	1079,60
 FONDO StrideUp 120x60 47 ^{11/16} x23 ^{11/16} "	9mm	2	1,44	28,28	36	51,84	1038,15
 DECORO Rigo 120x60 47 ^{11/16} x23 ^{11/16} "	9mm	2	1,44	28,44	36	51,84	1043,84
 FONDO StrideUp / ANTISLIP 80x80 31 ^{11/16} x31 ^{11/16} "	9mm	2	1,28	25,65	40	51,20	1046,08
 FONDO StrideUp 80x40 31 ^{11/16} x15 ^{11/16} "	9mm	4	1,28	24,75	24	30,72	614,07
 FONDO StrideUp 60x60 23 ^{11/16} x23 ^{11/16} "	9mm	4	1,44	28,98	30	43,20	889,56
 FONDO StrideUp / ANTISLIP not rectified 30x60 11 ^{11/16} x23 ^{11/16} "	9mm	8	1,44	27,86	32	46,08	911,77
 Dehors 80x80 31 ^{11/16} x31 ^{11/16} "	20mm	1	0,64	28,34	40	25,60	1153,68
 Dehors 120x60 47 ^{11/16} x23 ^{11/16} "	20mm	1	0,72	32,19	36	25,92	1174,01
 MOSAICO LISTELLO 28,5x28,8 11 ^{11/16} x11 ^{11/16} "	9mm	5	0,41	7,10	-	-	-
 MOSAICO FOGLIE 27,3x31,6 10 ^{11/16} x12 ^{11/16} "	9mm	6	0,51	9,31	-	-	-
 MOSAICO 30x30 11 ^{11/16} x11 ^{11/16} "	9mm	12	1,08	20,80	30	32,40	644,00
 FELCE 120x60 47 ^{11/16} x23 ^{11/16} "	9mm	2	1,44	30,50	20	28,82	630,00
 GRADONE CON TORO 120x33x4 47 ^{11/16} x13 ^{11/16} x1/4"	9mm	2	0,79	18,40	16	12,67	314,40
 BATTISCOPA 7x60 2 ^{11/16} x23 ^{11/16} "	9mm	10	0,42	8,18	72	30,23	608,96
 ELEMENTO A "L" incollato ANTISLIP 16,5x80x4,5 6 ^{11/16} x31 ^{11/16} x1/4"	9mm	2	0,26	6,18	48	12,67	316,92

Manufacturer Details:

European Ceramics Approved

BPIR COMPLIANT

Importer Details:



European Ceramic Tiles Ltd

Address: 7A Cowley Place, Rosedale, AKL 0632

NZBN: 9429037294571

Website: euroceramics.co.nz

Conforming to Standards EN 14411 ISO 13006 APPENDICE G GRUPPO Bia UGL con Ev ≤ 0,5%

CARATTERISTICA TECNICA PHYSICAL PROPERTIES TECHNISCHE DATEN CARACTÉRISTIQUE TECHNIQUE	METODOCA DI PROVA TESTING METHOD PRÜFVERFAHREN NORME D'ESSAIS	REFERIMENTO NORMA REFERENCE STANDARD REFERENZ NORME STANDARDWERTE	Valore Prodotto PRODUCT VALUES PRODUKT WERTE VALEUR PRODUIT	
			70x e N x 15 cm (mm)	N x 15 cm (%) (mm)
 Dimensioni Sizes Abmessungen Dimensions	EN ISO 10545-2	Lunghezza e larghezza - Length and width - Länge und Breite Longueur et largeur	±0,9	±0,6 ±2,0
		Spessore - Thickness - Stärke - Epaisseur	±0,5	±5,0 ±0,5
		Rettifinità spigoli - Linearity - Kantengeradheit - Rectitude des arêtes	±0,75	±0,5 ±1,5
		Ortogonalità - Wedging - Rechtwinkigkeit - Orthogonalité	±0,75	±0,5 ±2,0
		Planarità - Warpage - Ebenföchigkeit - Planité	±0,75	±0,5 ±2,0
Aspetto: percentuale di piastrelle accettabili nel lotto - appearance: percentage of acceptable tiles, per lot oberflächenbeschaffenheit; präsentatz der fliesen, die den geforderten eigenschaften entsprechen - aspect: pourcentage de carreaux acceptables sur		95 % min.	95 % min.	-
 Assorbimento d'acqua % - Water absorption % Wasseraufnahme % - Absorption d'eau %	EN ISO 10545-3	Ev ≤ 0,5N		Conforme - Conforming Erfüllt - Conforma
 Resistenza alla flessione - Modulus of rupture Biegezugfestigkeit - Résistance à la flexion	EN ISO 10545-4	Valore medio 35 N/mm ² min.		Conforme - Conforming Erfüllt - Conforma
Stato di rottura - Breakage resistance Bruchlast - Résistance à la rupture		sp. > 75 mm: min 1900 N sp. < 75 mm: min 700 N		Conforme - Conforming Erfüllt - Conforma
 Resistenza all'abrasione profonda - Scratch resistance Bestimmung des Widerstandes gegen tiefen Verschleib - Résistance à l'abrasion	EN ISO 10545-6	175 mm ³ max.		Medio - Average Mittelwert - Moyenne ± 150 mm ³
 Coefficiente di dilatazione termica lineare - Thermal expansion coefficient - Wärmeausdehnung - Coefficient de dilatation thermique linéaire	EN ISO 10545-8	Valore dichiarato - Declared value - Valeur déclaré - Valor declarado		6,8 MK-1
 Resistenza agli sbalzi termici - Thermal shock resistance - Temperaturstoßbeständigkeit - Résistance aux écarts de température	EN ISO 10545-9	Test superato in accordo con ISO 10545-1 - Pass according to ISO 10545-1 Pv en accord avec norme en 10545-1 - Test überstanden nach ISO 10545-1		* Resistente - Resistant Widerstandsfähig - Résistants
 Resistenza al gelo - Frost resistance Frostbeständigkeit - Résistance au gel	EN ISO 10545-12	Test superato in accordo con ISO 10545-1 - Pass according to ISO 10545-1 Pv en accord avec norme en 10545-1 - Test überstanden nach ISO 10545-1		* Resistente - Resistant Widerstandsfähig - Résistants
Resistenza a basse concentrazioni di acidi e alcali Resistance to low concentrations of acids and alkalis - Résistance à des basses concentrations d'acides et de bases - Beständigkeit gegen schwach konzentrierte säuren und laugen		Valore dichiarato - Declared value - Valeur déclaré - Angegebener Wert		* Resistente - Resistant Widerstandsfähig - Résistants
 Resistenza ad alte concentrazioni di acidi e alcali Resistance to high concentrations of acids and alkalis - Résistance à des hautes concentrations d'acides et de bases - Beständigkeit gegen stark konzentrierte säuren und laugen	EN ISO 10545-13	Valore dichiarato - Declared value - Valeur déclaré - Angegebener Wert		* Resistente - Resistant Widerstandsfähig - Résistants
Resistenza ai prodotti chimici di uso domestico e agli additivi per piscine - Resistance to domestic chemicals and additives for swimming pools - Résistance aux prod. chimiques d'usage domestique et additifs pour piscines Beständigkeit gegen chemische haushaushälterische und zusatzstoffe für schwimmbäder		18 min.		18A
 Resistenza alle macchie di piastrelle non smaltate naturali - Stain resistance of unglazed mattes porcelain floor tiles - Beständigkeit vor angelauchten natur fliesen - Résistance aux taches des carreaux non émaillés naturel	EN ISO 10545-14	Valore dichiarato - Declared value - Valeur déclaré - Angegebener Wert		* Resistente - Resistant Widerstandsfähig - Résistants
 Resistenza allo sciorisciato Stain resistance Abriebfestigkeit Résistance au dérapage	EN 16185	Annex A		Valore disponibile a richiesta Value available upon request Wert auf Anfrage verfügbar Valeur disponible sur demande
		Annex B		Valore disponibile a richiesta Value available upon request Wert auf Anfrage verfügbar Valeur disponible sur demande
	B.C.R.A. - D.M.235/89	Dove richiesto - if needed - Nach anforderung - Si demande		≥ 0,40 Dry / ≥ 0,40 Wet
	ANSI A328.3 D CCF	Dove richiesto - if needed - Nach anforderung - Si demande		≥ 0,42 Wet

Manufacturer Details:
 European Ceramics Approved
 BPIR COMPLIANT

Importer Details:
 European Ceramic Tiles Ltd
 Address: 7A Cowley Place, Rosedale, AKL 0632
 NZBN: 9429037294571
 Website: euroceramics.co.nz

Fire Resistance

The building code relating to fire rating regulations and standards requires specifiers to provide documentation such as fire certificates for materials used in construction.

Ceramics are in itself a fire-resistant material, mostly being manufactured at over 1200 degrees Celsius. Testing and providing such certification are therefore not relevant to the Ceramics industry.

Ceramic and Porcelain tiles are an inert material, and therefore non-combustible. They do not release fumes or toxic gases in the event of a fire. Porcelain tiles contain no sealants, waxes or other chemicals that could release VOC's into the environment. Ceramics do not pose a risk of spreading or intensifying a fire therefore there is no testing required as they do not contribute to a fire.

EXTRAORDINARY EFFECTS DURING USE PHASE:

Fire: According to /EN 13501-1:2007+A1:2009/, ceramic tiles can be classified as A1 class of fire resistance rating, because they do not contribute to fire.

It has been demonstrated that the coating of the ceramic tiles, in case of fire, reduces heat on them and thus the risk of collapse.

Water: Ceramic tiles cannot react with water because they are an insoluble material.

For further information on the physio-characteristics of fire resistance for tiles please refer to the Technical Documents section on euroceramics.co.nz

Manufacturer Details:
European Ceramics Approved
BPIR COMPLIANT

Importer Details:
European Ceramic Tiles Ltd
Address: 7A Cowley Place, Rosedale, AKL 0632
NZBN: 9429037294571
Website: euroceramics.co.nz